

GENERATORS

DELCO-REMY GENERATOR INDEX AND SPECIFICATIONS

Generator Number Note ①	Brush Spring Tension, Ounces		Direction of Rotation Note ②	Field Current at 6 Volts (Amperes)	Maximum Cold Output (Note ③)			Maximum Hot Output (Note ④)		
	Main	Third			Amperes	Volts	R. P. M.	Amperes	Volts	R. P. M.
405	25	None	CL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
417	25	17	CL	1.37-1.50⑤	26	13.0	1600	18	13.0	3000
419	25	17	CL	1.37-1.50⑤	26	13.0	1600	18	13.0	3000
434	25	17	CL	1.3-1.4⑦	10	7.45	⑧	⑧	⑧
440	25	17	CCL	1.37-1.50⑤	26	13.0	1600	18	13.0	3000
469	25	None	CL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
504	25	None	CL	1.43-1.58⑤	80	13.0	800	⑥	⑥	⑥
507	25	None	CCL	1.43-1.58⑤	57	13.0	650	⑥	⑥	⑥
518	25	None	CL	1.43-1.58⑤	57	13.0	650	⑥	⑥	⑥
519	25	None	CL	1.43-1.58⑤	80	13.0	800	⑥	⑥	⑥
522	25	None	CL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
525	25	None	CL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
527	25	None	CL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
530	25	None	CCL	1.17-1.30⑤	50	13.0	1700	⑥	⑥	⑥
534	25	None	CL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
535	25	None	CL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
538	25	None	CL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
539	25	None	CCL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
550	25	17	CL	1.37-1.50⑤	26	13.0	1600	18	13.0	3000
552	25	17	CCL	1.3	10	7.45	2100	⑧	⑧	⑧
553	25	17	CL	1.37-1.50⑤	26	13.0	1600	18	13.0	3000
555	25	17	CL	1.37-1.50⑤	26	13.0	1600	18	13.0	3000
556	25	17	CL	1.37-1.50⑤	26	13.0	1600	18	13.0	3000
557	25	17	CL	1.37-1.50⑤	15	13.0	1200	10	13.0	3000
560	25	None	CCL	1.12-1.23⑧	14	26.0	1000	⑥	⑥	⑥
561	25	17	CCL	1.37-1.50⑤	26	13.0	1600	18	13.0	3000
563	25	17	CL	2.3-2.6	27	9.0	3000	23	8.7	3200
564	25	17	CL	3.53-3.75	32	7.0	1000	24	7.0	1200
567	25	17	CL	3.5-3.75	40	7.0	1500	32	7.0	1700
568	25	17	CL	1.37-1.50⑤	26	13.0	1600	18	13.0	3000
600	20	17	CL	1.9-2.1⑨	11	15.1	1200	8.5	14.6	1300
601	25	17	CL	1.9-2.1⑨	21	13.0	1600	16	13.0	1600
602	20	17	CL	1.5-1.6⑨	11	15.1	1400	10.5	15.0	1400
603	25	None	CL	1.33-1.45⑤	20	13.0	950	⑥	⑥	⑥
604	25	17	CL	3.53-3.75	32	7.0	1000	24	7.0	1200
605	25	None	CL	1.33-1.45⑤	20	13.0	950	⑥	⑥	⑥
606	25	None	CL	1.33-1.45⑤	33	13.0	950	⑥	⑥	⑥
607	25	None	CL	1.33-1.45⑤	40	13.0	1250	⑥	⑥	⑥
608	25	None	CL	3.53-3.75	40	7.0	950	⑥	⑥	⑥
609	25	None	CL	3.53-3.75	40	7.0	950	⑥	⑥	⑥
610	25	None	CL	1.17-1.30⑤	50	13.0	1700	⑥	⑥	⑥
611	25	None	CL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
613	25	None	CCL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
614	25	None	CL	1.58-1.71	50	7.5	800	⑥	⑥	⑥
616	25	17	CCL	3.53-3.75	32	7.0	1000	24	7.0	1200
618	25	None	CCL	1.46-1.62⑩	55	13.0	950	⑥	⑥	⑥
622	25	None	CL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
625	25	None	CL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
630	25	None	CL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
633	25	None	CCL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
634	25	None	CCL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
637	25	None	CL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
639	25	None	CL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
670	25	None	CCL	3.53-3.75	40	7.0	950	⑥	⑥	⑥
671	25	None	CL	3.53-3.75	40	7.0	950	⑥	⑥	⑥
672	25	None	CL	1.37-1.50⑤	40	13.0	1400	⑥	⑥	⑥
673	25	None	CL	3.53-3.75	40	7.0	950	⑥	⑥	⑥
674	25	17	CL	3.53-3.75	32	7.0	1000	24	7.0	1200
676	25	17	CL	1.37-1.50⑤	26	13.0	1600	18	13.0	3000
677	25	17	CCL	1.37-1.50⑤	26	13.0	1600	18	13.0	3000

GENERATORS

DELCO-REMY GENERATOR INDEX AND SPECIFICATIONS

Generator Number Note (1)	Brush Spring Tension, Ounces		Direction of Rotation Note (2)	Field Current at 6 Volts (Amperes)	Maximum Cold Output (Note (3))			Maximum Hot Output (Note (4))		
	Main	Third			Amperes	Volts	R. P. M.	Amperes	Volts	R. P. M.
678	25	None	CL	1.37-1.50(5)	40	13.0	1400	(6)	(6)	(6)
679	25	None	CL	3.53-3.75	40	7.0	950	(6)	(6)	(6)
680	25	None	CL	3.53-3.75	40	7.0	950	(6)	(6)	(6)
682	25	None	CL	1.33-1.45(5)	33	13.0	950	(6)	(6)	(6)
683	25	None	CL	1.33-1.45(5)	33	13.0	950	(6)	(6)	(6)
687	25	17	CL	1.37-1.50(5)	26	13.0	1600	18	13.0	3000
689	25	None	CL	3.53-3.75	40	7.0	950	(6)	(6)	(6)
690	25	None	CL	1.33-1.45(5)	33	13.0	950	(6)	(6)	(6)
691	25	None	CL	1.37-1.50(5)	40	13.0	1400	(6)	(6)	(6)
692	25	None	CL	1.33-1.45(5)	40	13.0	1250	(6)	(6)	(6)
693	25	None	CL	1.33-1.45(5)	40	13.0	1250	(6)	(6)	(6)
694	25	None	CL	1.33-1.45(5)	33	13.0	950	(6)	(6)	(6)
695	25	17	CL	1.37-1.50	26	13.0	1600	18	13.0	3000
696	25	None	CL	1.33-1.45(5)	33	13.0	950	(6)	(6)	(6)
697	25	None	CL	1.37-1.50(5)	40	13.0	1400	(6)	(6)	(6)
698	25	None	CL	1.37-1.50(5)	40	13.0	1400	(6)	(6)	(6)
699	25	None	CL	1.33-1.45(5)	40	13.0	1250	(6)	(6)	(6)
916-A	25	None	CL	1.7- 2.0	25(7)	8.0	1250	(6)	(6)	(6)
916-B	25	None	CL	1.48-1.56(5)	17	14.75	1250	(6)	(6)	(6)
916-D	25	None	CL	1.7- 2.0	25(7)	8.0	1250	(6)	(6)	(6)
916-F	25	None	CL	1.7-2.0	26	8.0	1325	(6)	(6)	(6)
916-G	25	None	CL	1.48-1.56(5)	17	14.75	1250	(6)	(6)	(6)
916-H	25	None	CL	1.7-2.0	26	8.0	1325	(6)	(6)	(6)
916-J	25	None	CL	1.25-1.45(5)	17	14.75	1250	(6)	(6)	(6)
916-K	25	None	CL	1.7-2.0	26	8.0	1325	(6)	(6)	(6)
925-F	25	17	CL	2.7-3.0	33	8.0	1800	29	8.0	1900
925-G	25	17	CCL	2.7-3.0	33	8.0	1800	29	8.0	1900
925-H	25	17	CL	2.7-3.0	33	8.0	1800	29	8.0	1900
927-X	25	17	CL	2.3-2.5(5)	18	13.0	2200	15	13.0	2600
928-B	25	None	CL	1.08-1.15(5)	17	14.75	1650	(6)	(6)	(6)
930-C	25	None	CCL	1.08-1.15(5)	17	14.75	1650	(6)	(6)	(6)
930-D	25	None	CL	1.8-2.3	26	8.0	1450	(6)	(6)	(6)
930-E	25	None	CL	1.08-1.15(5)	17	14.75	1650	(6)	(6)	(6)
930-G	25	None	CL	1.8-2.3	28	8.0	1450	(6)	(6)	(6)
930-H	25	None	CL	1.8-2.3	26	8.0	1450	(6)	(6)	(6)
931-J	25	17	CL	3.5-4.0	24	8.8	1500	16	7.9	1800
931-M	25	17	CL	1.5-1.8	26	9.1	2300	20	8.4	2500
931-R	25	17	CL	3.5-4.0	24	8.8	1500	16	7.9	1800
931-T	25	17	CL	3.5-4.0	24	8.8	1500	16	7.9	1800
931-X	25	17	CL	1.05-1.15	19	8.4	1800	14	7.8	2100
932-A	25	17	CL	2.7-3.0	28	9.4	1900	24	8.9	2100
932-B	25	17	CL	3.5-4.0	24	8.8	1500	16	7.9	1800
932-D	25	17	CL	3.5-4.0	24	8.8	1500	16	7.9	1800
933-D	25	17	CL	1.7-2.0	10.5	7.5	5000	10.5	7.5	5000
934-A	25	None	CL	1.7-2.0	25(7)	8.0	1250	(6)	(6)	(6)
934-B	25	None	CL	1.48-1.56(5)	17	14.75	1250	(6)	(6)	(6)
934-C	25	None	CCL	1.7-2.0	25(7)	8.0	1250	(6)	(6)	(6)
934-D	25	None	CCL	1.48-1.56(5)	17	14.75	1250	(6)	(6)	(6)
934-E	25	None	CL	1.7-2.0	25(7)	8.0	1250	(6)	(6)	(6)
934-F	25	None	CL	1.7-2.0	26	8.0	1325	(6)	(6)	(6)
934-G	25	None	CL	1.48-1.56(5)	17	14.75	1250	(6)	(6)	(6)
934-H	25	None	CL	1.7-2.0	25(7)	8.0	1250	(6)	(6)	(6)
934-J	25	None	CL	1.48-1.56(5)	17	14.75	1250	(6)	(6)	(6)
934-M	25	None	CL	1.7-2.0	25(7)	8.0	1250	(6)	(6)	(6)
934-N	25	None	CL	1.48-1.56(5)	17	14.75	1250	(6)	(6)	(6)
934-P	25	None	CL	1.7-2.0	25(7)	8.0	1250	(6)	(6)	(6)
934-R	25	None	CL	1.48-1.56(5)	17	14.75	1250	(6)	(6)	(6)
934-S	25	None	CL	1.7-2.0	25(7)	8.0	1250	(6)	(6)	(6)
934-T	25	None	CL	1.48-1.56(5)	17	14.75	1250	(6)	(6)	(6)
934-U	25	None	CL	1.7-2.0	25(7)	8.0	1250	(6)	(6)	(6)

GENERATORS

DELCO-REMY GENERATOR INDEX AND SPECIFICATIONS

Generator Number Note (1)	Brush Spring Tension, Ounces		Direction of Rotation Note (2)	Field Current at 6 Volts (Amperes)	Maximum Cold Output (Note (3))			Maximum Hot Output (Note (4))		
	Main	Third			Amperes	Volts	R. P. M.	Amperes	Volts	R. P. M.
934-V	25	None	CL	1.48-1.56(1)	17	14.75	1250	(1)	(1)	(1)
934-W	25	None	CL	1.7-2.0	25(1)	8.0	1250	(1)	(1)	(1)
934-X	25	None	CL	1.48-1.56(1)	17	14.75	1250	(1)	(1)	(1)
934-Y	25	None	CL	1.7-2.0	25(1)	8.0	1250	(1)	(1)	(1)
934-Z	25	None	CL	1.7-2.0	26	8.0	1325	(1)	(1)	(1)
935-D	25	17	CL	2.3-2.6	21	8.5	2600	15	7.9	2800
935-P	25	17	CL	2.3-2.6	21	8.5	2600	15	7.9	2800
935-V	25	17	CL	2.3-2.6	23	8.8	2800	20	8.5	3400
935-Z	25	17	CL	2.3-2.6	20	8.5	2400	17	8.1	3000
936-A	25	17	CL	2.3-2.6	23	8.8	2800	20	8.5	3400
936-B	25	17	CCL	2.3-2.6	23	8.8	2800	20	8.5	3400
936-H	25	17	CL	2.3-2.6	23	8.8	2800	20	8.5	3400
936-M	25	17	CL	2.3-2.6	23	8.8	2800	20	8.5	3400
936-U	25	17	CL	2.3-2.6	27	9.0	3000	23	8.7	3200
936-Y	25	17	CL	2.3-2.6	23	8.8	2800	20	8.5	3400
936-Z	25	17	CL	2.3-2.6	23	8.8	2800	20	8.5	3400
937-G	25	17	CL	3.5-4.5	17	8.15	1900	13	7.75	2100
937-H	25	17	CL	3.5-4.5	18	8.3	2000	15	8.0	2400
937-P	25	17	CL	3.5-4.5	22	8.6	2400	15	7.9	2600
937-R	16	17	CL	3.5-4.5	10	7.4	1700	9	7.3	1800
937-V	25	17	CL	3.5-4.5	18	8.25	2300	14	7.85	2500
937-Y	25	17	CL	3.5-4.5	18	8.3	2000	15	8.0	2400
937-Z	25	17	CL	3.5-4.5	18	8.3	2000	15	8.0	2400
938-B	16	17	CL	4.6-6.0	22	8.6	1600	12	7.6	2000
938-E	16	17	CL	4.6-6.0	17	8.2	1500	12	7.6	1600
939-H	16	17	CL	3.3-4.0(1)	10	14.8	1500	7	14.2	1600
939-J	25	17	CL	3.3-4.0(1)	18	16.3	2000	15	16.0	2200
939-M	16	17	CL	3.3-4.0(1)	10	14.8	1500	7	14.2	1600
939-U	16	17	CL	4.6-6.0	21	8.5	1900	12	7.6	2200
939-V	16	17	CL	3.3-4.0(1)	10	14.8	1500	7	14.2	1600
939-Y	16	17	CL	3.3-4.0(1)	10	14.8	1500	7	14.2	1600
941-F	16	17	CL	4.6-6.0	22	8.6	1600	12	7.6	2000
941-H	16	17	CCL	4.6-6.0	22	8.6	1600	12	7.6	2000
941-J	16	17	CL	4.6-6.0	15	7.9	1500	8	7.2	1800
941-N	16	17	CL	4.6-6.0	22	8.6	1600	12	7.6	2000
941-S	16	17	CL	4.6-6.0	22	8.6	1600	12	7.6	2000
941-T	16	17	CCL	4.6-6.0	22	8.6	1600	12	7.6	2000
941-W	16	17	CL	4.6-6.0	22	8.6	1600	12	7.6	2000
941-Z	16	17	CL	4.0-6.1	19	8.3	1450	10	7.4	2000
942-H	17	17	CL	4.6-6.0	17	7.3	1900	12	7.6	2200
943-J	16	17	CL	3.5-4.5	17	8.2	2000	13	7.7	2200
943-R	25	17	CL	3.5-4.5	17	8.2	2300	14	7.6	2400
943-V	16	17	CL	3.5-4.5	17	8.2	2000	13	7.7	2200
943-X	25	17	CL	0.95-1.2	10.5	8.5	2400	8	8.5	2500
943-Z	17	17	CL	4.6-6.0	17	8.2	1900	13	7.7	2200
945-D	16	17	CL	4.0-5.4	20	8.4	1600	13	7.7	2000
945-L	16	17	CL	2.8-3.5	26	9.2	1900	16	8.0	2200
945-N	16	17	CL	2.8-3.5	26	9.2	1900	16	8.0	2200
945-S	16	17	CCL	2.7-3.0(1)	13	15.5	1700	9	14.4	2000
945-T	16	17	CL	4.0-5.4	20	8.4	1600	13	7.7	2000
945-V	16	17	CCL	2.7-3.0(1)	13	15.5	1700	9	14.4	2000
946-B	25	17	CL	3.5-4.5	22	8.6	2400	15	7.9	2600
946-C	16	17	CL	3.5-4.5	17	8.2	2000	13	7.7	2200
946-D	16	17	CL	3.5-4.5	17	8.2	2000	13	7.7	2200
946-G	25	17	CL	3.5-4.5	18	8.3	2000	15	8.0	2400
946-H	25	17	CL	3.5-4.5	22	8.6	2400	15	7.9	2600
946-J	16	17	CL	3.5-4.5	17	8.2	2000	13	7.7	2200
946-N	16	17	CL	3.5-4.5	17	8.2	2000	13	7.7	2200
946-P	16	17	CL	3.5-4.5	17	8.2	2000	13	7.7	2200
946-S	16	17	CL	3.5-4.5	17	8.2	2000	13	7.7	2200

GENERATORS

DELCO-REMY GENERATOR INDEX AND SPECIFICATIONS

Generator Number Note ①	Brush Spring Tension, Ounces		Direction of Rotation Note ②	Field Current at 6 Volts (Amperes)	Maximum Cold Output (Note ③)			Maximum Hot Output (Note ④)		
	Main	Third			Amperes	Volts	R. P. M.	Amperes	Volts	R. P. M.
948-C	25	17	CL	2.3-2.6	23	8.8	2800	20	8.5	3400
948-F	25	17	CL	2.3-2.6	20	8.5	2400	17	8.1	3000
948-G	25	17	CL	2.3-2.6	27	9.0	3000	25	8.7	3200
948-H	25	17	CL	2.3-2.6	27	9.0	3000	23	8.7	3200
948-K	25	17	CL	2.3-2.6	20	8.5	2400	17	8.1	3000
948-M	25	17	CL	4.6-6.0	22	8.6	1600	12	7.6	2000
948-N	25	17	CL	2.3-2.6	23	8.8	2800	20	8.5	3400
948-P	25	17	CCL	2.3-2.6	23	8.8	2800	20	8.5	3400
948-R	25	17	CL	2.3-2.6	23	8.8	2800	20	8.5	3400
948-V	25	17	CL	2.3-2.6	20	8.5	2400	17	8.1	3000
952	25	None	CL	1.46-1.62⑤	55	13.0	950	⑥	⑥	⑥
953-D	16	17	CL	4.6-6.0	22	8.6	1600	12	7.6	2000
953-G	16	17	CL	4.6-6.0	22	8.6	1600	12	7.6	2000
953-Y	16	17	CL	4.6-6.0	22	8.6	1600	12	7.6	2000
955	25	None	CCL	1.46-1.62⑤	55	13.0	950	⑥	⑥	⑥
955-E	17	17	CL	4.6-6.0	22	8.6	1600	12	7.6	2000
956	25	None	CCL	1.46-1.62⑤	55	13.0	950	⑥	⑥	⑥
956-C	16	17	CL	4.0-5.4	22	8.6	1500	12	7.6	1800
956-D	16	17	CL	4.0-5.4	22	8.6	1500	12	7.6	1800
956-E	16	17	CL	4.0-5.4	22	8.6	1500	12	7.6	1800
956-F	16	17	CL	1.9-2.2	19	8.3	1800	15	7.9	2100
956-H	25	17	CL	3.5-4.5	22	8.6	2400	15	7.9	2600
956-J	16	17	CL	1.9-2.2	19	8.3	1800	15	7.9	2100
956-K	16	17	CL	1.9-2.2	19	8.3	1800	15	7.9	2100
956-P	16	17	CCL	2.5-3.0⑤	13	15.6	1800	10	14.8	2000
957-B	16	17	CL	4.0-5.4	20	8.4	1600	13	7.7	2000
957-M	16	17	CL	2.7-3.0⑤	14	15.7	1700	10	14.6	2000
957-T	16	17	CL	4.0-5.4	20	8.4	1600	13	7.7	2000
957-W	16	17	CL	2.8-3.5	21	8.6	1800	14	7.8	1900
957-X	16	17	CL	2.7-3.0⑤	14	15.7	1700	10	14.6	2000
957-Y	25	17	CL	1.9-2.2	19	8.3	1800	15	7.9	2100
957-Z	16	17	CCL	2.8-3.5	26	9.2	1900	16	8.0	2200
958-A	25	17	CL	2.8-3.5	20	8.5	2000	17	7.9	2100
958-C	25	17	CL	2.8-3.5	20	8.5	2000	17	7.9	2100
958-D	25	17	CL	2.8-3.5	20	8.5	2000	17	7.9	2100
958-E	25	17	CL	2.8-3.5	20	8.5	2000	17	7.9	2100
959-B	16	17	CCL	3.3-4.0⑤	10	14.8	1500	7	14.2	1600
959-L	16	17	CL	4.6-6.0	22	8.6	1600	12	7.6	2000
960	25	None	CL	1.46-1.62⑤	55	13.0	950	⑥	⑥	⑥
960-A	25	17	CL	2.3-2.6	27	9.0	3000	23	8.7	3200
960-B	25	17	CCL	2.3-2.6	23	8.8	2800	20	8.5	3400
960-C	25	17	CL	2.3-2.6	23	8.8	2800	20	8.5	3400
960-D	25	17	CL	2.3-2.6	23	8.8	2800	20	8.5	3400
960-E	25	17	CL	2.3-2.6	25	9.1	3000	20	8.5	3200
960-F	17	17	CL	3.5-4.5	22	8.6	2400	15	7.9	2600
960-G	25	17	CL	2.3-2.6	27	9.0	3000	23	8.7	3200
960-H	25	17	CL	2.3-2.6	23	8.8	2800	20	8.5	3400
960-J	25	17	CCL	2.3-2.6	23	8.8	2800	20	8.5	3400
961	25	None	CCL	1.46-1.62⑤	55	13.0	950	⑥	⑥	⑥
962	25	None	CCL	1.58-1.71	40	7.5	675	⑥	⑥	⑥
963	25	None	CL	1.17-1.30⑤	40	13.0	1100	⑥	⑥	⑥
964	25	None	CL	1.46-1.62⑤	55	13.0	950	⑥	⑥	⑥
965-A	16	17	CCL	1.37-1.50⑤	26	13.0	1600	18	13.0	3000
965-F	25	17	CL	2.5-3.0⑤	13	15.6	1800	10	14.8	2000
965-J	16	17	CL	2.8-3.5	26	9.2	1900	16	8.0	2200
965-L	16	17	CL	4.0-5.4	20	8.4	1600	13	7.7	2000
965-R	25	17	CL	3.0-3.7	19	8.4	1800	15	8.0	2100
965-S	16	17	CL	4.0-5.4	20	8.4	1600	13	7.7	2000
965-U	16	17	CL	4.0-5.4	20	8.4	1600	13	7.7	2000
965-W	16	17	CL	2.8-3.5	26	9.2	1900	16	8.0	2200
965-Z	16	17	CL	2.5-3.0⑤	10	15.5	1700	7	14.9	2000
966	25	None	CL	1.46-1.62⑤	55	13.0	950	⑥	⑥	⑥
967-G	16	17	CL	1.9-2.2	19	8.3	1800	15	7.9	2100
967-R	25	17	CL	4.0-5.4	20	8.4	1600	13	7.7	2000
967-S	25	17	CCL	2.8-3.5	25	9.0	1800	16	8.0	2100